

19* OSRAM™ 4-In-1 CWWW LEDs + Zoom

ProPar™ Z19 CWWW LED fixtures offer superior white color mixing abilities and brightness thanks to its 19* 15-watt, high power CWWW OSRAM™ LEDs, and its 5°-60° degree zoomable beam angle is an awesome dual function wash/beam effect to add to any light show! Like the other lights in our ProPar™ line, it also sports a rugged cast aluminum chassis and provides exceptional quality, coverage and ease of use at a MUCH lower price than other fixtures in its class.

Users have the ability to run built-in programs and perform finely tunable CWWW color mixing with or without DMX control, the ProPar™ Z19 CWWW is perfect for architectural work and installs as well. Two mounting yokes add positioning flexibility, and a slew of built-in programs in DMX allow the it to be programmed with ease.

In DMX mode, you can control the fixture with either 5/7 or 9-channels. You'll have full control of many features such as CWWW color mixing, strobe, dimmer, and 30 built-in programs. The 4-button LED control panel also allows total control over the fixture including auto run settings, sound active mode, and CW/CW/WW/WW color balance settings!

This fixture is available with either black or white housing, and matching barndoors are available (sold separately.)

Main Features

- WW/WW/CW/CW color mixing w/19x 15W OSRAM LEDs
- Available with black or white housing plus optional barndoors (sold separately)
- 5°-60° degree zoomable beam angle
- Variable electronic dimming & strobe
- Built-in color & chase + zoom macros via DMX
- Built-in automated programs via master/slave
- Built-in sound active programs
- Color mixing ability in standalone mode
- 5/7 or 9-channel DMX control modes
- Easy-to-use 4-button LED control panel menu display
- Dual mounting brackets for positioning flexibility
- Rugged and well-built (It hits the gym regularly)
- 3-pin male & female DMX input/output
- PowerCon™ compatible AC power In/Out connectors

PROPAR Z19™



Light Source

- 19x OSRAM® 15W 4-in-1 CWWW LEDs

Control

- USITT DMX-512
- 5/7 or 9-channels
- 3-pin XLR male/female input/output
- Standalone, master/slave, auto, sound active

Optical

- 5°-60° degree zoomable beam angle
- Luminous Intensity: 28,177 Lux @ 2M (narrow), 5,400 Lux @ 5M (narrow), 4,386 Lux @ 2M (wide)

Power

- Operating Voltage: 90-250VAC, 50-60 Hertz
- Power Consumption: 175W, 1.65A, PF: .98

Operating Temperature

- Max. Operating Temp.: 104 degrees F (40 degrees C) ambient

Dimensions

- Width: 10.5 inches (268 mm)
- Depth: 8.1 inches (206 mm)
- Height: 10.6 in. (270 mm), 13.7 in. (348 mm) w/brackets
- Weight: 11.5 lbs (5.2 kg)

Warranty

- 2-year limited warranty, does not cover malfunction caused by damage to LEDs.