



Available IP Flex Extension Cables



NEW

ÉPIX Flex 20 is a durable, outdoor-rated LED flexible strip that extends 5 meters and can be cut and prolonged without compromising its IP67 rating. This allows it to line even the most complicated spaces. 240 individually controllable RGB LEDs allow for a variety of color-changing options that can be dimmed and brightened as you see fit, and pixel-mapped for showing video and/or motion graphics. The unit's reliable plug-and-play 24 V system allows for 75ft of extension between the first ÉPIX Flex 20 and the ÉPIX Flex Drive, which is required for operation and controls up to eight ÉPIX Flex 20 strips. Expect versatile control options including DMX, Art-Net and sACN (streaming ACN) and reduced programming time by tapping into alternate personalities of 17 channel or the pixel personality 720 channels) for use with video servers. 10 mounting brackets are included to ease use in a variety of permanent installations like nightclub or architectural entertainment venues.

Item Code: EPIXFLEX20

OUTPUT	
Source	240 LEDs (tri-color RGB)
Pixel Pitch	20 mm
Viewing Angle	160°
ELECTRICAL	
Voltage Range	24 VDC
Power Consumption 120 V, 60 Hz	79 W, 0.653 A
Power Consumption 208 V, 60 Hz	93 W, 0.450 A
Power Consumption 230 V, 50 Hz	95 W, 0.417 A
Linking	2 ÉPIX Flex 20 (per port) (4 total) (without ÉPIX Flex Boost); 2 additional ÉPIX Flex 20 (per port) (8 total)
CONTROL	
Required Controller	ÉPIX Flex Drive
Control Channels	720
PHYSICAL	
Dimensions	196.85 x 0.55 x 0.2 in (5,000 x 14 x 5 mm)
Weight	1.2 lb (0.6 kg)
Power/Control Connection	3-pin IP65 FLEX
Mounting	15 mm mounting brackets with screws (included)
LISTINGS	
Certification(s)	CE, MET
Environment	IP67, outdoor/wet use
ACCESSORIES	
Included	Mounting brackets, Termination kit
Required	ÉPIX Flex Drive
OPTIONAL ACCESSORIES	
Software	ArKaos Media Master Express + KN software
Data Cabling	3-pin IP65 FLEX cable pigtails for power/data output