



KRAMER

C-BM/BM

BNC Coax Video Cable

| 3G HD-SDI - BNC



Kramer's C-BM/BM is constructed of high performance RG-6 cable with 75Ω BNC connectors at each end. It offers outstanding quality, durability, and high performance for any video signal application

FEATURES

Quality Construction - RG-6 cable for the highest resolution signals

High-Quality Connectors - True 75Ω BNC connectors maintain correct impedance end-to-end

Varied Selection of Lengths - Available in versions of 1.5 to 150ft (0.5 to 45.7m)

Cable Specs - Tested to 3G. For detailed cable specs, see Kramer BC-1X



KRAMER

TECHNICAL SPECIFICATIONS

Conductor:	18 AWG solid bare copper
Dielectric:	Skin foam
Shield:	(A) 61% braid 34 AWG aluminum wire. (B) Dual foil/Mylar 25% overlap rate
Outside Jacket:	PVC
Outside Jacket Color:	Dark gray with white lettering
Center Conductor:	1.02mm (0.0403in)
Dielectric:	4.57mm (0.179in)
Outside Diameter:	6.95mm (0.391in)
Impedance:	75Ω
DC Resistance:	21.8Ω/km (6.6Ω/1000ft)
Capacitance:	53.1pF/m (16.1pF/ft)
Velocity of Propagation:	82%
Temperature:	-20° to 75°C (-4° to 167°F)
Attenuation (dB/100 ft.):	-0.3dB @1MHz -0.6dB @5MHz -0.8dB @10MHz -1.6dB @50MHz -2.0dB @100MHz -2.8dB @180MHz -4.4dB @400MHz -5.7dB @750MHz -6.7dB @1000MHz
UL:	CL2
CSA:	C(UL) CL2



KRAMER

CONFIGURATIONS

C-BM/BM-1.5	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-3	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-6	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-10	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-15	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-25	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-35	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-50	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-75	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-100	1 BNC (M) to 1 BNC (M) RG-6 Video Cable
C-BM/BM-150	1 BNC (M) to 1 BNC (M) RG-6 Video Cable